



GST NO.: 29AHZPU5620Q1ZZ

An ISO 9001:2015 Certified Company

ROYAL INDUSTRIAL SUPPLIERS

QUALITY FASTENERS SPECIALIST



8310165941 / 9959457863



sales@royalfastenersindia.com



www.royalfastenersindia.com

TECHNICAL DATA SHEET

CSK PHILLIPS SCREW



MATERIAL- STAINLESS STEEL


GRADE-SS304 (A2-70)

AS PER-ISO-5856/IS-15437

CATALOGUE NO. R4A21H

INSTALLATION GUIDE

- SELECT THE CORRECT SIZE OF CSK PHILLIPS SCREW AND MATCHING PHILLIPS SCREWDRIVER.
- ENSURE THE COUNTERSUNK HOLE IS PREPARED TO MATCH THE SCREW ANGLE FOR FLUSH FITTING.
- CLEAN THE MATING SURFACE AND HOLE TO REMOVE ANY DUST, OIL, OR DEBRIS.
- POSITION THE COMPONENTS IN PROPER ALIGNMENT BEFORE INSERTING THE SCREW.
- PLACE THE CSK PHILLIPS SCREW INTO THE COUNTERSUNK HOLE BY HAND TO START THREADING.
- INSERT THE PHILLIPS SCREWDRIVER INTO THE CROSS SLOT OF THE SCREW HEAD.
- TURN THE SCREWDRIVER CLOCKWISE WHILE APPLYING EVEN PRESSURE.
- ENSURE THE SCREW HEAD SITS FLUSH WITH THE MATERIAL SURFACE AFTER TIGHTENING.
- DO NOT OVERTIGHTEN TO PREVENT THREAD DAMAGE OR MATERIAL CRACKING.
- USE A TORQUE SCREWDRIVER IF SPECIFIC TORQUE VALUES ARE REQUIRED.
- INSPECT THE INSTALLED SCREW TO CONFIRM A SECURE AND FLUSH FIT.



Dia	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25
Head Dia D nom	5.60	8.05	10.05	12.10	16.10
Head Dia D max	6.05	7.50	9.50	11.40	15.10
Head Dia D min	5.35	7.15	8.95	10.70	14.50
Head Height H	1.27	1.69	2.12	2.54	3.39
BIT	PH2	PH2	PH2	PH2	PH3

Quote the PART NUMBER given below with your order/ inquiries:

All Dimensions in mm

Length↓ Size→	M3x0.5	M4x0.7	M5x0.8	M6x1.0	M8x1.25
4	R4A21H03104				
5	R4A21H03105	R4A21H04105	R4A21H05105		
6	R4A21H03106	R4A21H04106	R4A21H05106	R4A21H06106	
8	R4A21HH03108	R4A21H04108	R4A21H05108	R4A21H06108	R4A21H08108
10	R4A21HH03110	R4A21H04110	R4A21H05110	R4A21H06110	R4A21H08110
12	R4A21H03112	R4A21H04112	R4A21H05112	R4A21H06112	R4A21H08112
14	R4A21H03114	R4A21H04114	R4A21H05114	R4A21H06114	R4A21H08114
16	R4A21H03116	R4A21H04116	R4A21H05116	R4A21H06116	R4A21H08116
18	R4A21H03118	R4A21H04118	R4A21H05118	R4A21H06118	R4A21H08118
20			R4A21H05120	R4A21H06120	R4A21H08120

Sizes in BLUE are non-preferred. Availability is limited and MOQ is applied. *Data is strictly informative*

Note: All Austenitic Stainless-Steel Fasteners may exhibit some Magnetic Properties due to the Manufacturing Process.
Refer: ISO 3506-2 Annex F